





trusted support www.yday

The MEWA - special purpose stroller is designed for children who are unable to walk or sit in the correct position as a result of injury or another condition.

With adjustable pads, the backrest can be optimized to the child's needs and will provide the right security. Large wheels (gel-filled or pumped), with shock absorbers of rear as well as front wheels, facilitate comfortable travel on uneven ground.

the stroller offers a high seat comfort thanks to tilt in space and recline - so-called CRADLE, which will help you to put the child in the right position, making sure that the pressure is

Mewa is also fitted with a table that can be used for feeding, exercising or playing. Abduction belts stabilize the pelvis and secure the child from sliding out of the buggy.

why MEWA?

Foldable frame and removable seat

The construction of main elements of the stroller allows to disassemble it into 2 separate units (frame and seat) - give yourself considerably more space!

4 Reversible seat

The construction of the stroller allows to easily rotate the seat opposite to the driving direction.

SEAT MINIMIZING KIT wide range of additional accessories

A set of 4 separate, specially designed pads allows to perfectly adjust the stroller to the user needs. Additionally a variety of additional accessories considerably enhances user comfort create and enjoy your own set!

2 CRADLE function -**INCREDIBLY ERGONOMIC**

The stroller offers a practical function of tilting the seat together with backrest giving your child safe and the most ergonomic position during any travel.

a wide range of equipment



SEAT MINIMIZING KIT FIVE-POINT SAFETY BELTS

RAINCOVER MOSOUITO NET



ADJUSTABLE CANOPY WITH

WINDOW

SHOCK ABSORBERS FOR WHEELS **CENTRAL BREAK** DIRECTIONAL LOCK OF FRONT WHEELS





THERAPEUTIC TABLE

TECHNICAL DATA OF STROLLER READY TO TRAVEL







footrest adjustable within 19 - 29 cm



total weight 23 kg



total lenght 111 cm



total height 120 cm



total width 65 cm

USER PARAMETERS



growth 90 - 125 cm



maximum weight 35 kg

* with regulation inserts